Distributed by:

JAMECO® ELECTRONICS

www.Jameco.com ✦ 1-800-831-4242

The content and copyrights of the attached material are the property of its owner.

ON Semiconductor™

Amplifier Transistors
NPN Silicon

2N5550
2N5551*

*ON Semiconductor Preferred Device

MAXIMUM RATINGS

Rating	Symbol	2N5550	2N5551	Unit
Collector–Emitter Voltage	V_{CEO}	140	160	Vdc
Collector–Base Voltage	V_{CBO}	160	180	Vdc
Emitter–Base Voltage	V_{EBO}	6.0		Vdc
Collector Current — Continuous	I_C	600		mAdc
Total Device Dissipation @ T_A = 25°C Derate above 25°C	P_D	625 5.0		mW mW/°C
Total Device Dissipation @ T_C = 25°C Derate above 25°C	P_D	1.5 12		Watts mW/°C
Operating and Storage Junction Temperature Range	T_J, T_{stg}	–55 to +150		°C



CASE 29–11, STYLE 1
TO–92 (TO–226AA)



THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Thermal Resistance, Junction to Ambient	$R_{\theta JA}$	200	°C/W
Thermal Resistance, Junction to Case	$R_{\theta JC}$	83.3	°C/W

ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted)

Characteristic		Symbol	Min	Max	Unit
OFF CHARACTERISTICS					
Collector–Emitter Breakdown Voltage[1] (I_C = 1.0 mAdc, I_B = 0)	 2N5550 2N5551	$V_{(BR)CEO}$	 140 160	 — —	Vdc
Collector–Base Breakdown Voltage (I_C = 100 μAdc, I_E = 0)	 2N5550 2N5551	$V_{(BR)CBO}$	 160 180	 — —	Vdc
Emitter–Base Breakdown Voltage (I_E = 10 μAdc, I_C = 0)		$V_{(BR)EBO}$	6.0	—	Vdc
Collector Cutoff Current (V_{CB} = 100 Vdc, I_E = 0) (V_{CB} = 120 Vdc, I_E = 0) (V_{CB} = 100 Vdc, I_E = 0, T_A = 100°C) (V_{CB} = 120 Vdc, I_E = 0, T_A = 100°C)	 2N5550 2N5551 2N5550 2N5551	I_{CBO}	 — — — —	 100 50 100 50	 nAdc μAdc
Emitter Cutoff Current (V_{EB} = 4.0 Vdc, I_C = 0)		I_{EBO}	—	50	nAdc

1. Pulse Test: Pulse Width = 300 μs, Duty Cycle = 2.0%.

Preferred devices are ON Semiconductor recommended choices for future use and best overall value.

© Semiconductor Components Industries, LLC, 2001

June, 2001 – Rev. 1
Publication Order Number:
2N5550/D

ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted) (Continued)

Characteristic		Symbol	Min	Max	Unit
ON CHARACTERISTICS(1)					
DC Current Gain		h_{FE}			—
(I_C = 1.0 mAdc, V_{CE} = 5.0 Vdc)	2N5550		60	—	
	2N5551		80	—	
(I_C = 10 mAdc, V_{CE} = 5.0 Vdc)	2N5550		60	250	
	2N5551		80	250	
(I_C = 50 mAdc, V_{CE} = 5.0 Vdc)	2N5550		20	—	
	2N5551		30	—	
Collector–Emitter Saturation Voltage		$V_{CE(sat)}$			Vdc
(I_C = 10 mAdc, I_B = 1.0 mAdc)	Both Types		—	0.15	
(I_C = 50 mAdc, I_B = 5.0 mAdc)	2N5550		—	0.25	
	2N5551		—	0.20	
Base–Emitter Saturation Voltage		$V_{BE(sat)}$			Vdc
(I_C = 10 mAdc, I_B = 1.0 mAdc)	Both Types		—	1.0	
(I_C = 50 mAdc, I_B = 5.0 mAdc)	2N5550		—	1.2	
	2N5551		—	1.0	
SMALL–SIGNAL CHARACTERISTICS					
Current–Gain — Bandwidth Product (I_C = 10 mAdc, V_{CE} = 10 Vdc, f = 100 MHz)		f_T	100	300	MHz
Output Capacitance (V_{CB} = 10 Vdc, I_E = 0, f = 1.0 MHz)		C_{obo}	—	6.0	pF
Input Capacitance		C_{ibo}			pF
(V_{EB} = 0.5 Vdc, I_C = 0, f = 1.0 MHz)	2N5550		—	30	
	2N5551		—	20	
Small–Signal Current Gain (I_C = 1.0 mAdc, V_{CE} = 10 Vdc, f = 1.0 kHz)		h_{fe}	50	200	—
Noise Figure		NF			dB
(I_C = 250 μAdc, V_{CE} = 5.0 Vdc, R_S = 1.0 kΩ,	2N5550		—	10	
f = 1.0 kHz)	2N5551		—	8.0	

1. Pulse Test: Pulse Width = 300 μs, Duty Cycle = 2.0%.



Figure 1. DC Current Gain



Figure 2. Collector Saturation Region



Figure 3. Collector Cut−Off Region



Figure 4. “On” Voltages



Figure 5. Temperature Coefficients



Values Shown are for I_C @ 10 mA

Figure 6. Switching Time Test Circuit



Figure 7. Capacitances



Figure 8. Turn–On Time



Figure 9. Turn–Off Time

PACKAGE DIMENSIONS

TO–92 (TO–226)
CASE 29–11
ISSUE AL





SECTION X–X

NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. CONTOUR OF PACKAGE BEYOND DIMENSION R IS UNCONTROLLED.
4. LEAD DIMENSION IS UNCONTROLLED IN P AND BEYOND DIMENSION K MINIMUM.

	INCHES		MILLIMETERS	
DIM	MIN	MAX	MIN	MAX
A	0.175	0.205	4.45	5.20
B	0.170	0.210	4.32	5.33
C	0.125	0.165	3.18	4.19
D	0.016	0.021	0.407	0.533
G	0.045	0.055	1.15	1.39
H	0.095	0.105	2.42	2.66
J	0.015	0.020	0.39	0.50
K	0.500	---	12.70	---
L	0.250	---	6.35	---
N	0.080	0.105	2.04	2.66
P	---	0.100	---	2.54
R	0.115	---	2.93	---
V	0.135	---	3.43	---

YLE 1:
PIN 1. EMITTER
2. BASE
3. COLLECTOR

Notes

Notes

ON Semiconductor and are trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer.

PUBLICATION ORDERING INFORMATION

Literature Fulfillment:
Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303–675–2175 or 800–344–3860 Toll Free USA/Canada
Fax: 303–675–2176 or 800–344–3867 Toll Free USA/Canada
Email: ONlit@hibbertco.com

N. American Technical Support: 800–282–9855 Toll Free USA/Canada

JAPAN: ON Semiconductor, Japan Customer Focus Center
4–32–1 Nishi–Gotanda, Shinagawa–ku, Tokyo, Japan 141–0031
Phone: 81–3–5740–2700
Email: r14525@onsemi.com

ON Semiconductor Website: http://onsemi.com

For additional information, please contact your local Sales Representative.